

TrackMaster Plus™

Premium quality 100% acrylic emulsion fortified with rubber particles designed for coating asphalt and latex/rubber running track surfaces. TrackMaster Plus™ is available in attractive colors using the SportMaster® ColorPlus™ System. TrackMaster Plus™ contains rubber granules. Squeegee, brush or spray application.

PRODUCT #	DESCRIPTION	Sq. Ft. COVERAGE	WT.	PRICE
C1740K	Neutral 30-gal. keg	1500	290 lbs.	\$349.99
C1740D	Neutral 55-gal. drum	2750	550 lbs.	\$552.99
C1709K	Red 30-gal. keg	1500	290 lbs.	\$447.99
C1709D	Red 55-gal. drum	2750	550 lbs.	\$726.99

Mixing Procedures:

Neutral TrackMaster Plus™	55 gallons
Water	13-14 gallons
ColorPlus™ Pigment Dispersion (see page 75)	4 gallons

Mix and apply with soft rubber squeegee.

Material Requirements (coverage - 50 sf/gal):

Approximately .15 to .20 gallon per square yard per coat depending on surface porosity.

TrackMaster™

A polymer modified asphalt emulsion fortified with rubber particles designed for coating asphalt running tracks. Beautifies tracks and provides superior protection against oxidation, ravelling, and moisture penetration. **Available in black only.**



PRODUCT #	DESCRIPTION	Sq. Ft. COVERAGE	WT.	PRICE
C1700K	30-gal. keg	1500	300 lbs.	\$247.99
C1700D	55-gal. drum	2750	575 lbs.	\$348.99
C1700B	Bulk pricing available on request			

Mixing Procedures:

TrackMaster™	55 gallons
Water	15-17 gallons

Mix and apply with soft rubber squeegee or spray.

Material Requirements (coverage - 50 sf/gal):

Approximately .15 to .20 gallon per square yard per coat depending on surface porosity.

Lane One™

A 100% acrylic trowel grade patching material fortified with sand and rubber. Ideal for repairing running lanes and field event runways and pads. Also used for filling cracks up to 1" wide. Lane One is Black, but can be coated with TrackMaster Plus to match surface color of track area.



PRODUCT #	DESCRIPTION	WT.	PRICE
C1750P	5-gal. pail	51 lbs.	\$ 58.99
C1750K	30-gal. keg	305 lbs.	\$366.99
C1750D	55-gal. drum	545 lbs.	\$584.99

Mixing Procedures:

Use as is. Do not dilute. Apply with soft rubber squeegee.

Material Requirements (coverage):

Approximately 1 gallon per square yard at 1/8" depth. Ultimate coverage will be dependent upon depth of repair.

TrackFlex™ Crack Sealant

Acrylic elastomeric pourable crack sealant designed for sealing cracks up to 1/2" wide in asphalt or latex/rubber track surfaces. TrackFlex is black, but can be coated with TrackMaster Plus to match surface color of track area.



PRODUCT #	DESCRIPTION	WT.	PRICE
C1760G	1-gal. jug	10 lbs.	\$ 28.99
C1760P	5-gal. pail	47 lbs.	\$115.99

Mixing Procedures:

Apply as is. Do not dilute. Smooth flush with rubber squeegee.

Material Requirements (coverage):

Typically, one gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack.