



Specifications for applying the
**TrackMaster Plus Rubberized Surface Coating
over asphalt running track surfaces**

CMT - 28

Revised: 7/09

PRODUCT NAME:

TrackMaster Plus
Rubberized Surface
Coating Over Asphalt
Running Track Surfaces

MANUFACTURER:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477
www.thorworks.com

Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

1. SCOPE:

1.1

The following specifications pertain to the application of the TrackMaster Plus Rubberized Surface Coating over asphalt running track surfaces. Refer to Product Data Sheets for specific mixing and application instructions.

2. SURFACE PREPARATION:

2.1

New asphalt surfaces must cure 14 to 30 days prior to application. The surface must be cleaned entirely of dust, dirt, debris, and all loose materials.

2.2

Existing oxidized surfaces should be primed with Acrylic Adhesion Promoter.

2.3

Fill all cracks with Lane One patch material or TrackFlex pourable crack sealant.

2.4

Fill depressions and damaged areas with Lane One patch material.

3. APPLICATION OF TRACKMASTER PLUS RUBBERIZED COATING:

3.1

Over properly prepared track surface apply a minimum of two coats of TrackMaster Plus in accordance with manufacturer's mixing and application instructions.

4. LINE MARKINGS:

4.1

Line markings shall be laid out and applied by qualified technicians in accordance with the chosen governing rules.

5. GENERAL:

5.1

All work shall be performed in a workmanlike manner. All containers and debris shall be removed from job when completed.

TrackMaster Plus Rubberized Surface Coating
over asphalt running track surfaces
CMT - 28

SealMaster
July 2009
Supersedes: CMT-28 (7/04)

SPORT SURFACING