

MATERIAL SAFETY DATA SHEET

(In compliance with OSHA Regulation 29 CFR 1910.1200 - Hazard Communication)

IDENTITY: SportMaster Acrylic Resurfacer with Sand - Black Product Number: C1330
--

SECTION I - Manufacturer / Product Information

Manufacturer's Name: SealMaster Industries, Inc.	Emergency Telephone No.: Chemtrec: 1-800-424-9300
Address: 2520 South Campbell Street Sandusky, Ohio 44870	Telephone Number for Information: 1-419-626-4375
Date Prepared: November 2, 1995	

SECTION II - Hazardous Ingredients / Identity Information

Hazardous Components: Specific Chemical Identity; Common Name, CAS No.)	Exposure Limits		Other Limits Recommend.	% (Optional)
	OSHA PEL -(1)	ACGIH TLV -(2)		
Silicon Dioxide dust SiO ₂ CAS #14808-60-7	0.1 mg/m ³			60.0-62.4

(*) Indicate toxic chemical subject to the reporting requirement of section 313 of SARA Title III and 40 CFR 372 (Code of Federal Regulations). (A chemical or chemical category listed by the EPA is subject to toxic chemical release reporting under the Emergency Planning and Community Right-To-Know Act of 1986). There are no components in this formulation subject to this reporting requirement.

(1) (OSHA Permissible Exposure Limit) - These limits express the permissible maximum amount of a chemical to which a person may be exposed. The concentrations listed refer to airborne exposure, as might occur (via mist) which is unlikely to form with this product in view of its properties and intended use.

(2) (American Conference of Governmental Industrial Hygienists' Threshold Limit Value) - This value is expressed in parts per million. The TLV is the concentration of substance in the air that can be breathed for five consecutive eight hour workdays (40-hour work week) by most people, without harmful effects.

(3) The silicon dioxide dust, that is listed as a hazardous ingredient is based on OSHA regulation for respirable (airborne) dust. Since this product is a wet application item, there is virtually no hazard associated with its use in its original form. There would be potential hazards associated with the silicon dioxide dust during operations such as sandblasting and scarification. Approximately one percent of sand content is considered respirable.

SECTION III - Physical / Chemical Characteristics

Boiling Point: 100 ^o Celsius (212 ^o Fahrenheit)
Specific Gravity (Water = 1): 1.68
Vapor Pressure (mm Hg): Not determined; expected to be very close to that of water.
Melting Point: N/A
Vapor Density: < 1 (Lighter than air)
Evaporation Rate (Butyl Acetate = 1): < 1 (Slower than butyl acetate)
Solubility in Water: This formulation is water dilutable in its liquid state, after drying it is not water soluble.
Appearance: Black colored liquid
Odor: Slightly ammonia

SECTION IV - Fire and Explosion Hazard Data**HMIS Rating:** 0**Flash Point (Method Used):** Non Combustible**Flammable Limits in Air:** Not Applicable**Extinguishing Media:** Foam, CO₂, dry chemical, water fog, other.**Special Fire Fighting Methods:** Full protective equipment, including self-contained breathing apparatus, to be worn.**Unusual Fire & Explosion Hazards:** Not Applicable**SECTION V - Reactivity Data****HMIS Rating:** 0**Stability:** Good storage stability between 5^o and 50^o Celsius.**Conditions to Avoid:** Keep from freezing and extreme heat.**Incompatibility (Materials to Avoid):** None known**Hazardous Decomposition or Byproducts:** Combustion may yield carbon monoxide and/or carbon dioxide, and traces of monomer, as well as other toxic pyrolysis products.**Hazardous Polymerization:** Will not occur.**SECTION VI - Health Hazard Data****HMIS Rating:** 0**Primary Routes of Exposure:****Inhalation:** Yes**Eye Contact:** Yes**Skin Contact:** No**Ingestion:** Yes**Health Hazards (Acute & Chronic):** (Acute): Dizziness, weakness, nausea, headache.
(Chronic): Gastrointestinal irritation.**Signs and Symptoms of Exposure:****Inhalation:** Vapor could cause headache, dizziness, weakness and nausea.**Eye:** Eye irritation, watering, and redness.**Skin:** The liquid is not easily absorbed**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.**Medical Conditions Generally Aggravated by Exposure:** None known.**Carcinogenicity: National Toxicology Program (NTP):** No**International Agency for Research on Cancer (IARC) Monographs:** No**OSHA Regulated:** No**Emergency and First Aid Procedures:****Inhalation:** Remove to fresh air and provide oxygen if breathing is difficult.**Ingestion:** If conscious, give 1 - 2 glasses of water or milk and induce vomiting with Syrup of Ipecac, keeping head below hips to avoid aspiration into lungs. (Vomiting is most effective if initiated within 30 minutes of ingestion). CONTACT A PHYSICIAN FOR HELP.**Skin Contact:** Wash area with soap and water. Remove contaminated clothing.**Eye Contact:** Irrigate eyes immediately with large amounts of room temperature water for at least 15 minutes, or until eye is clear. TAKE TO A PHYSICIAN FOR HELP.

SECTION VII - Precautions for Safe Handling and Use

Steps To Be Taken In Case Material Is Released Or Spilled: Dike and contain spill with inert material (sand, sawdust, diatomaceous earth, etc.). Pump liquid into storage tanks. Remaining liquid may be taken up with inert materials. Place in closed container for proper disposal.

Waste Disposal Method: Dispose of in accordance with Local, State, and Federal regulations.

Precautions To Be Taken In Handling And Storing: Keep container closed and upright to prevent leakage. Avoid freezing or temperatures above 50^o Celsius.

Other Precautions: Do not take internally. Keep away from children. Avoid breathing vapors. For external use only.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type): None should be required. Use OSHA / NIOSH approved respirator in poorly ventilated areas.

Ventilation: Local Exhaust: Use if needed to control vapor.

Mechanical General: N/A

Special: N/A

Other: N/A

Protective Gloves: Rubber gloves for prolonged contact.

Eye Protection: Chemical splash goggles recommended to avoid eye contact.

Other Protective Clothing or Equipment: A rubber apron is recommended to protect clothing during application.

Work / Hygienic Practices: Wash hands before eating.

SECTION IX - Special Precautions

Other Precautions: Do not apply when rain is imminent or forecast, or within 60 minutes of a rain, to prevent contamination of runoff water.

SECTION X - Disclaimer

All information, recommendations, and suggestions concerning this product are based upon tests, literature references, and/or calculations, believed to be reliable. The manufacturer makes no guarantee, expressed or implied, as to the affect of use, or the safety and toxicity of the product. The information contained in this sheet cannot be taken as the sum total of all protective measures to be taken.