Revised: 7/04



# CourtFlex

## 1. PRODUCT NAME:

CourtFlex

#### 2. MANUFACTURER:

ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 Phone: 800-326-1994 Fax: 419-626-5477 www.thorworks.com

#### **Additional Plant Locations:**

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

# 3. PRODUCT DESCRIPTION & BENEFITS:

An elastomeric cold pour crack sealant designed for use in cracks on sport and recreational pavement surfaces. Use to seal cracks up to 1/2" in width. Maintains excellent flexibility, elasticity and adhesion at temperatures as low as -15°F on asphalt and concrete surfaces.

**Color:** Available in green, red, and neutral colors.

**Uses:** Tennis courts, basketball courts, play areas, and all-purpose sport surfaces.

# 4. SURFACE PREPARATION:

Cracks must be cleaned of dust, dirt, and debris including vegetation. Blow clean with an air compressor or high pressure washer. Fill deep cracks with sand to within 3/4" of surface.

# 5. APPLICATION:

Use product as is. Do not dilute. Pour into crack until it is filled completely. Set time is dependant upon temperature, humidity and sealer thickness. For best results, apply on dry surface when surface temperature is not expected to drop below 50°F or exceed 120°F. Material must be at or below surface level when application is completed. Before material sets up, scrape excess from surface and use a rubber squeegee (rounded

or V-shaped preferably), to assure below surface contour of finished application.

CMT - 8

#### 6. COVERAGE:

Approximately 150-200 linear feet of 1/2" wide x 1/2" deep cracks.

**7. CLEAN UP:** Wash tools in water. If material has dried, use kerosene.

### 8. CAUTIONS:

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use.

#### 9. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as weather, workmanship, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed. Copyright© 2004, SealMaster All rights reserved.

ThorWorks Industries, Inc. P.O. Box 2277 Sandusky, OH 44870

Phone: 1-800-326-1994 FAX: 1-419-626-5477

www.sportmaster.net