



Lane One

CMT - 16

Revised: 4/05

1. PRODUCT NAME:

Lane One

2. MANUFACTURER:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477
www.thorworks.com

Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS:

Lane One is a trowel grade Acrylic patching material fortified with sand and rubber particles. Lane One is designed for filling cracks and smoothing rough areas up to 1/8" depth on rubberized asphalt running tracks.

Color: Black

Uses: For minor repair of rubberized asphalt running tracks.

4. SURFACE PREPARATION:

Track surface shall be cleaned entirely of dust, dirt, debris and all loose material. New asphalt track surface must cure 30 days before application.

5. MIXING PROCEDURES:

For patching and filling depressions use Lane One as is from container without dilution. For use with a squeegee, Lane One may be diluted with water to achieve workability.

6. APPLICATION:

Apply Lane One with a trowel, straight edge, or squeegee. For depressions greater than 1/8", Lane One shall be applied in multiple lifts not to exceed 1" total depth.

7. IMPORTANT:

Stir material thoroughly before using. Temperature must be a minimum of 50° F. and rising before

application. Do not apply when raining is imminent or forecast. Keep from freezing. Close container when not in use.

8. COVERAGE:

Approximately 4 gallons per square yard at 1" depth.

9. DRYING TIME:

Patches should be allowed to dry 24 hours.

10. CAUTIONS:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

11. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work

performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2005 SealMaster
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477

www.sportmaster.net

Lane One
CMT-16

SealMaster
April 2005
(Supersedes CMT-16 (6/97), CMT-16 (7/04))

SPORT SURFACING

Product Data:

Type	Acrylic Emulsion
Odor	Slight Ammonia
Flammability.....	Non Flammable
Flash Point	None
Storage Life	One Year