



# Ready-Mix Color

CMT - 37

Revised: 7/09

## 1. PRODUCT NAME:

Ready-Mix Color

## 2. MANUFACTURER:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477  
www.thorworks.com

### Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit [www.sealmaster.net](http://www.sealmaster.net) to find the location near you.

## 3. PRODUCT DESCRIPTION & BENEFITS:

SportMaster Ready-Mix Color is a 100% acrylic emulsion coating designed for tennis courts and other sport and recreational pavement surfaces.

**Color:** Available in Forest Green, \*Light Green, Dark Green, Beige, Brown, \*Red, Maroon, Gray, and Blue.

LEED: SS Credit 7.1:  
Heat Island Effect: Non-Roof  
\*Specific colors may contribute toward LEED credits.

**Uses:** Tennis courts, basketball courts, and other asphalt or concrete multi-purpose surfaces.

## 4. SURFACE PREPARATION:

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials. Repair of pavement surface defects, depressions and cracks must be completed prior to application. All repairs must be flush and smooth to adjoining surfaces.

**New asphalt surfaces** must cure 14 to 28 days prior to application. It is recommended that any uncoated asphalt surface receive one or more coats of Acrylic Resurfacer (Technical Bulletin CMT-3) as required by surface roughness and porosity to provide a smooth, dense underlayment for

application of color texture and finish coats.

**New concrete surfaces** must cure 28 days prior to application. Concrete surfaces should have a medium broom finish or similar roughened texture. They must never be steel trowelled. Etch surface with Muriatic or Phosphoric Acid and apply SportMaster Acrylic SportMaster Adhesion Promoter prior to color coating.

## 5. MIXING PROCEDURES:

Ready-Mix Color is ready to use. Do not add water. Stir thoroughly prior to application.

## 6. APPLICATION:

Apply Ready-Mix Color with a soft rubber squeegee. Allow each coat to thoroughly dry before applying the next coat. Two coats are recommended.

## 7. IMPORTANT:

Stir material thoroughly before using. Temperature must be a minimum of 50° F. and rising before application. Do not apply when raining is imminent or forecast. Keep from freezing. Close container when not in use.

## 8. COVERAGE:

Approximately .12 to .15 gallon per square yard per coat.

## 9. DRYING TIME:

Ready-Mix Color dries in 30 to 60 minutes under optimum drying conditions. Allow 48 hours before allowing foot traffic or play.

## 10. CAUTIONS:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15

minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

## 11. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2009, SealMaster  
All rights reserved.

ThorWorks Industries, Inc.  
P.O. Box 2277  
Sandusky, OH 44870

Phone: 1-800-326-1994  
FAX: 1-419-626-5477

[www.sportmaster.net](http://www.sportmaster.net)

### Product Data:

|                   |                   |
|-------------------|-------------------|
| Type              | Acrylic           |
| Odor .....        | Slight Ammonia    |
| Flammability..... | Non Flammable     |
| Flash Point ..... | None              |
| Colors.....       | Several Available |