

# STRIPE-RITE

**CMT-14**

REVISED 12/19

## PRODUCT DESCRIPTION & BENEFITS

Stripe-Rite is a 100% acrylic clear drying emulsion primer for line striping. Stripe-Rite is applied prior to SportMaster Line Paint to fill the minor voids between the masking tape and the court surface to assure crisp, razor sharp lines.

## USES

For priming line markings on any asphalt, concrete or color coated surface.

## COLOR

Milky White. Clear when dried.

| Chemical Characteristics |                    |
|--------------------------|--------------------|
|                          | % Weight (Nominal) |
| Acrylic Emulsion         | 38.0               |
| Hiding Pigment           | 0.0                |
| Mineral Inert Fillers    | 7.0                |
| Film Formers, Additives  | 1.5                |
| Water                    | 50.0               |

| Product Data              |                             |
|---------------------------|-----------------------------|
| Type                      | Acrylic Emulsion            |
| Pounds per gallon at 77°F | 8.9 ± .5                    |
| % Non Volatile Material   | 29 ± 5                      |
| Odor                      | Slight Ammonia              |
| Flammability              | Non-Flammable               |
| Flash Point               | None                        |
| Storage Life              | One Year                    |
| Colors                    | Milky White, clear when dry |

## SURFACE PREPARATION

Pavement Surface must be cleaned of dust, dirt, debris and all loose material.

## APPLICATION

Stripe-Rite can be applied by roller or brush. Allow Stripe-Rite to dry completely before applying SportMaster Line Paint.

## IMPORTANT

Surface and air temperatures must be above 50°F (10°C) during application and for at least 24 hours after application. Stir before using. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

## DRYING TIME

Thirty to sixty (30 to 60) minutes under optimum drying conditions. Indoor applications are substantially affected by temperature and available ventilation and will dry more slowly.

## COVERAGE

500 to 600 lineal feet of 2 inch line per gallon.

## CLEAN-UP

Wash tools in water before material dries.

## CAUTIONS

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. Refer to product Safety Data Sheet (SDS) for additional safety information and precautions.

## WARRANTY

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2019, SportMaster  
All rights reserved.

ThorWorks Industries, Inc.  
P.O. Box 2277  
Sandusky, OH 44870

Phone: 1-800-326-1994  
FAX: 1-419-626-5477  
www.sportmaster.net