

WHITE LINE PAINT

CMT-50

REVISED 12/19

USES

Line marking on tennis courts, basketball courts, pickleball courts, and other asphalt or concrete pavement surfaces.

COLOR

Available in white.

Product Data	
Type	Acrylic Emulsion
Pounds per gallon at 77°F	10.5 ± .5
% Non Volatile Material	49 ± 2
Odor	Ammonia
Flammability	Non-Flammable
Flash Point	None
Storage Life	One Year

SURFACE PREPARATION

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose material. If using White Line Paint on a new, uncoated surface, allow adequate curing time before application.

MIXING PROCEDURES

White Line Paint can be rolled or brushed. To assure crisp lines, it is advisable to use a high quality tape to mask lines. Remove tape as soon as White Line Paint has dried. White Line Paint can be modified to match the exact texture of the court surface by adding silica sand.

IMPORTANT

Stir before using. Temperatures must be above 50°F both during application and for a period of at least 24 hours after application. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. On outdoor concrete surfaces, assure adequate and functional perimeter drains as well as a sound vapor barrier beneath the slab.

DRYING TIME

Thirty to sixty (30 to 60) minutes under optimum drying conditions. Indoor applications are substantially affected by temperature and available ventilation and will dry more slowly.

COVERAGE

500 to 600 lineal feet of 2-inch line per gallon.

CAUTIONS

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. Refer to product Safety Data Sheet (SDS) for additional safety information and precautions.

WARRANTY

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2019, SportMaster
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477
www.sportmaster.net