#### ALL CATALOG PRICES ARE F.O.B. SANDUSKY, OHIO



## **ACRYLIC PATCH BINDER**

A 100% acrylic liquid binder designed for on-site mixing with sand and cement. Ideal for leveling and repairing low spots and depressions up to 1/2" deep on tennis court and other sport surface pavements.

NOTE: Patching Straightedges available on page 118.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1480P	5 - Gallon Pail	47 lbs.	\$ 184.99
C1480K	30 - Gallon Keg	280 lbs.	\$ 1,158.99
C1480D	55 - Gallon Drum	500 lbs.	\$ 2,019.99

#### MIXING PROCEDURES:

Acrylic Patch Binder	1 gallon
Sand (50-60 Mesh)	30 lbs.
Cement	6 lbs. (approximately 1/2 gallon)

**NOTE:** Thoroughly mix dry sand and cement together first before adding to Acrylic Patch Binder.

#### **MATERIAL REQUIREMENTS (coverage):**

One gallon will produce enough patch mix (when mixed with sand and cement) to fill .86 square yard (approximately 7.75 square feet) at 1/4" depth.





## **CRACKMAGIC™**

Premium grade heavy-bodied 100% acrylic elastomeric crack filler. Remains flexible at temperatures below zero. Available in neutral, green and red. Packaged four 1-gallon pails to a box or sold individually.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1590G	Neutral 1 - Gallon Pail	10 lbs.	\$ 71.99
C1570G	Green 1 - Gallon Pail	10 lbs.	\$ 71.99
C1580G	Red 1 - Gallon Pail	10 lbs.	\$ 71.99

#### MIXING PROCEDURES:

### MATERIAL REQUIREMENTS (coverage):

Use as is. Do not dilute.

Typically, one gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack.





## **ACRYLIC CRACK PATCH**

A 100% acrylic trowel grade crack filler. Fortified with sand for filling cracks up to 1" wide on tennis courts and other sport surface pavements. Available in red, green, blue or neutral. Packaged in four 1-gallon pails to a box or sold individually.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1520G	Neutral 1 - Gallon Pail	17 lbs.	\$ 30.99
C1500G	Green 1 - Gallon Pail	17 lbs.	\$ 30.99
C1510G	Red 1 - Gallon Pail	17 lbs.	\$ 30.99
C1515G	Blue 1 - Gallon Pail	17 lbs.	\$ 30.99

#### MIXING PROCEDURES:

#### MATERIAL REQUIREMENTS (coverage):

Use as is. Do not dilute.

Typically, one gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack.



# COURTFLEX™ CRACK SEALANT

A 100% acrylic elastomeric crack sealant designed for filling cracks up to 1/2" wide. Flexible down to -10° F. Available in red, green or neutral. Packaged six jugs to a box or sold individually.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1560G	Neutral 1 - Gallon Jug	10 lbs.	\$ 42.99
C1540G	Green 1 - Gallon Jug	10 lbs.	\$ 42.99
C1550G	Red 1 - Gallon Jug	10 lbs.	\$ 42.99

### MIXING PROCEDURES:

#### MATERIAL REQUIREMENTS (coverage):

Use as is. Do not dilute.

Typically, one gallon will fill approximately 150-200 feet of cracks depending on depth and width of crack.



# CLEAR CRACK SEALANT

Clear drying acrylic crack sealant for small cracks on sport surfaces. Keep cracks sealed on sport surfaces without seeing unsightly repairs.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1530G	1 - Gallon Pail	10 lbs.	\$ 66.99

#### MIXING PROCEDURES:

#### MATERIAL REQUIREMENTS (coverage):

Use as is. Do not dilute.

Typically, one gallon will fill approximately 150-200 feet of cracks depending on depth and width of crack.