

## WHITE LINE PAINT

A 100% acrylic water-based line paint highly pigmented for one coat coverage. Packaged in easy-to-use 1-gallon jugs with pour spouts, and 5-gallon pails. Available without or with sand [textured].

**NOTE:** See Line Taping Machine on page 115.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1600G	1 - Gallon Jug	12 lbs.	\$ 36.99
C1600P	5 - Gallon Pail	60 lbs.	\$ 141.99
C1620G	Textured 1 - Gallon Jug	13 lbs.	\$ 36.99
C1620P	Textured 5 - Gallon Pail	65 lbs.	\$ 141.99



**MIXING PROCEDURES:**

Use as is. Do not dilute.

**MATERIAL REQUIREMENTS (coverage):**

500-600 feet of 2" line per gallon.

## STRIPE RITE™

FOR SHARP LINES! A 100% acrylic, clear-drying emulsion primer that is applied prior to T/C line paint to fill the minor voids between the masking tape and court surface. Assures crisp, razor-sharp lines.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
C1610G	1 - Gallon Jug	10 lbs.	\$ 23.99
C1610P	5 - Gallon Pail	47 lbs.	\$ 85.99

**MIXING PROCEDURES:**

Use as is. Do not dilute.

**MATERIAL REQUIREMENTS (coverage):**

500-600 feet of 2" line per gallon.



## ACRYLIC ADHESION PROMOTER

100% acrylic emulsion primer designed to promote the adhesion of repair products and coatings. Apply by spray, roller, or brush. Ready to use.

PRODUCT #	DESCRIPTION	COVERAGE	WEIGHT	PRICE
C1650P	5 - Gallon Pail	1,250 sq. ft.	46 lbs.	\$ 68.99
C1650K	30 - Gallon Keg	7,500 sq. ft.	270 lbs.	\$ 420.99
C1650D	55 - Gallon Drum	13,750 sq. ft.	510 lbs.	\$ 678.99

**MIXING PROCEDURES:**

Use as is. Do not dilute.

**MATERIAL REQUIREMENTS (coverage):**

200-300 square feet per gallon.



## SPORTWAX™ CLEAR COAT

Clear drying, 100% acrylic top coat for tennis courts, basketball courts, and more. Extends the life of surface coatings. Apply by squeegee, lambswool applicator, or spray. SportWax Clear Coat is a ready-to-use product.

PRODUCT #	DESCRIPTION	COVERAGE	WEIGHT	PRICE
C1850P	5 - Gallon Pail	1250 sq. ft.	46 lbs.	\$ 86.99
C1850K	30 - Gallon Keg	7500 sq. ft.	270 lbs.	\$ 528.99
C1850D	55 - Gallon Drum	13750 sq. ft.	510 lbs.	\$ 860.99

**MIXING PROCEDURES:**

Use as is. Do not dilute.

**MATERIAL REQUIREMENTS (coverage):**

200-300 feet per gallon.