

LANE ONE

CMT-16

REVISED 12/19

PRODUCT DESCRIPTION & BENEFITS

Lane One is a trowel grade Acrylic patching material fortified with sand and rubber particles. Lane One is designed for filling cracks and smoothing rough areas up to 1/8" depth on rubberized asphalt running tracks.

USES

For minor repair of rubberized asphalt running tracks.

COLOR

Black. Can be coated over with TrackMaster Plus or suitable acrylic surfacing product for additional colors.

Product Data	
Type	Acrylic Emulsion
Odor	Slight Ammonia
Flammability	Non-Flammable
Flash Point	None
Storage Life	One Year

SURFACE PREPARATION

Track surface shall be cleaned entirely of dust, dirt, debris and all loose material. New asphalt track surface must cure 14-30 days before application.

MIXING PROCEDURES

For patching and filling depressions, use Lane One as is from container without dilution. For use with a squeegee, Lane One may be diluted with water to achieve workability.

APPLICATION

Apply Lane One with a trowel, straight edge, or squeegee. For depressions greater than 1/8", Lane One shall be applied in multiple lifts not to exceed 1" total depth.

IMPORTANT

Surface and air temperatures must be above 50°F (10°C) during application and for at least 24 hours after application. Stir before using. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

COVERAGE

Approximately 1 gallon per square yard at 1/8" depth.

DRYING TIME

Patches should be allowed to dry 24 hours.

CAUTIONS

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. Refer to product Safety Data Sheet (SDS) for additional safety information and precautions.

WARRANTY

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2019, SportMaster
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477
www.sportmaster.net